

JAX Rust Remover for use on iron and steel

Using JAX Rust Remover is simple:

- Prepare and clean the surface to be treated
- Apply the JAX Rust Remover
- Wash well with water and dry.

The JAX Rust Remover only removes rust on iron and steel. To ensure the best results, clean your metal of all oil, grease and wax. JAX manufactures metal cleaners that are optimal for prepping your metal, but there is no one cleaner that will guarantee perfection. Your choice of cleaner depends on what you are trying to remove from your metal. Regardless of what you use to clean your metal, we recommend using Dawn Dishwashing Liquid as the final step before applying the JAX Rust Remover. Before applying the solution, remove loose rust with a wire brush.

Wearing gloves is highly recommended as to not introduce oils from your hands to the metal. To be safe, eye protection is always recommended.

To apply, either brush solution on with a bristle brush or soaking the entire object in the JAX Rust Remover. Rinse the object with water and use a stiff brush to remove loose rust.

Do NOT dilute the JAX Rust Remover.

On particularly heavy rust, you may need to repeat the procedure a second time.

If the metal surface discolors, clean the object with one of the JAX Metal Cleaners. Use a polishing cloth to achieve your desired finish. Once you are happy with your finish, you may wax, oil, or Rust the metal as a final step, although in many cases leaving the metal "unprotected" may be desirable.

JAX products never expire, however, they can deteriorate over time if not cared for properly. Safety is the first priority. Always store JAX products at room temperature, in tightly closed original containers AND in a locked, safe place. Do not mix used product with fresh. Contaminating the original container will seriously reduce the shelf-life of the product.

Always use JAX Products in plastic or glass containers. When you dispose of used products and containers, please do so in at an approved waste disposal facility. Never reuse an empty JAX container.

Make sure to refer to the Safety Data Sheets for additional information before you begin. Do not mix JAX Products with any other chemicals.

Notes:

It is advisable to test the JAX Rust Remover in a small inconspicuous area to make sure that it does not adversely affect or damage the surface being treated.

To use the JAX Rust Remover as a pre-paint primer, soak metal in solution until rust is removed. DO NOT RINSE. Allow the JAX Rust Remover to air-dry before painting.